

ROGERS
NASHVILLE, TENNESSEE

AB SERIES – ALUMINUM



The **ROGERS ALUMINUM** series has become one of our most popular body models. This body has been designed with precision engineering and built with aircraft grade 6061 T6 aluminum extrusions. The floor is a combination 5454 H34 grade material in 1/4" thickness and 3/8" in the rear for excellent wear characteristics. The tailgate and hoist well are constructed of 5454 H34 1/4" material. Standard body lengths are between 16-21 feet, with custom lengths exceeding 24 feet. A sloped hoist-well along with an inside chamfer connecting side to floor allow for optimal cleaning when unloading materials. Additional features include large box-type 1/4" aluminum rear post for added corner strength; side sheets continuously welded to side and corner posts; sloping tailgate and sloping bottom rails. This body has over 40 years of performance and design enhancements making it the best of its kind.

"ROGERS - Another Word for Quality"

This has been our slogan as a trusted dump body manufacturer since 1946. Coast to coast, each ROGERS body is custom designed to match our customer's specific use.

Collaborate with our sales team to design and build the exact body that best suits your truck's needs.

SINCE 1946

www.rogersdumpbodies.com

MAIN: (615) 244-9720 | TOLL FREE: (877) 407-6437 | FAX: (615) 244-9719



STANDARD ALUMINUM BODY SPECIFICATIONS & MATERIAL:

- **CYLINDER:** Front telescopic
- **TARP:** electric tarp, aluminum arms and rubrail springs.
- **TAILGATE:** 3-section with two horizontal angled braces and with lower section vertical supports to protect panel surface; air actuated tailgate latch
- **SIDE & FRONT MATERIAL:** .160" 5454 H34 sheet welded to 6" box post extrusions
- **TOP RAIL:** Heavy duty 6" aluminum extrusion. 6" board pockets
- **SIDE SUPPORTS:** Sloping bottom rail extrusions interlocks to side and floor; 6" boxed vertical supports on approximate 24" centers
- **FRAME LONGITUDINAL:** 6" x 3" extruded channel longitudinal members
- **FRAME CROSS MEMEBERS:** C-channel spaced approximately 7.5" apart
- **LIGHTS:** Standard light package consists of LED marker lights to meet FMVSS #108 and rear post stop & turn LED lights
- **ADDITIONAL FEATURES:** 20" cabshield, rear rubber mudflaps, safety support strut, back-up alarm

NON STANDARD OPTIONAL EQUIPMENT

- Auxiliary Air Axles
- Hi-Lift Tailgate
- Various Asphalt Lip Lengths
- Multiple Cabshield Designs & Lengths
- Specialty In-Cab Controls
- PTO for Automatic Transmission
- Wood/Metal Sideboards
- Watertight Tailgate
- Pintle Hitches (15-50 Ton)
- Special Lighting & Paint Options
- Coal chute in tailgate
- Snow & Ice Setups for Plows/Spreaders
- Custom Side & Tailgate Heights
- .190" & .250" Material for Sides & Front
- Bushings & Grease Fittings in Top Tailgate Hardware

ROGERS AB SERIES TECHNICAL DATA

Length (ft.)	16	17	18	19	20	21
Model Number	160AB	170AB	180AB	190AB	200AB	210AB
Truck CA/CT* (in.)	126-144	138-156	150-166	162-176	call	call
Side Height (in.)	48	48	48	48	48	48
Tailgate Height (in.)	54	54	54	54	54	54
Cubic Capacity (cu yds)	16.4	17.5	18.6	19.7	20.8	21.9
Approximate Weight (lbs)	3645	3775	3875	3975	4095	4205



ROGERS trademark hydraulic hi-lift tailgate is an industry leader in design and performance.



Auxiliary air lift axles allow for increased GVWR and maximum payload.



Various size heights available to match the capacity needs of your truck.



www.rogersdumpbodies.com

MAIN: (615) 244-9720 | TOLL FREE: (877) 407-6437 | FAX: (615) 244-9719

